


NOTES:

1. LATERALS AND FITTINGS SHALL BE A MINIMUM OF SIX (6) INCHES IN DIAMETER. SERVICES AND FITTINGS SHALL BE A MINIMUM OF SIX (6) INCHES IN DIAMETER FOR SINGLE FAMILY RESIDENTIAL INSTALLATIONS AND SIX (6) INCHES IN DIAMETER FOR ALL OTHER INSTALLATIONS. SINGLE LATERALS ONLY SHALL BE ALLOWED.
2. ALL LATERALS SHALL EXTEND FROM THE SEWER MAIN TO ONE (1) FOOT OUTSIDE THE RIGHT-OF-WAY TERMINATING WITH A TWO-WAY CLEANOUT TO BE INSTALLED ONE (1) FOOT OUTSIDE THE RIGHT-OF-WAY BY THE CONTRACTOR. PAYMENT TO THE CITY FOR THE RIGHT-OF-WAY CLEANOUT SHALL BE MADE BY THE OWNER AS PART OF THE SEWER SERVICE CONNECTION FEE. THE RIGHT-OF-WAY CLEANOUT SHALL BE MAINTAINED BY THE OWNER.
3. IN ADDITION TO THE RIGHT-OF-WAY CLEANOUT, A CLEANOUT AT EACH BUILDING SHALL BE INSTALLED BY THE BUILDING CONTRACTOR.
4. FOR LOCATIONS WITH CURBING, ETCH THE LETTER "S" MINIMUM OF 2 INCHES HIGH AND 1/4 INCH DEEP IN FACE OF CURB, AND PAINT GREEN. FOR LOCATIONS WITHOUT CURBING BUT WITH SIDEWALK, ETCH THE LETTER "S" MINIMUM OF 2 INCHES HIGH AND 1/4 INCH DEEP IN FRONT OF SIDEWALK, AND PAINT GREEN. AS AN ALTERNATIVE TO ETCHING IN ALL LOCATIONS AND CONDITIONS, A STAINLESS STEEL DISC AND NAIL MAY BE USED. DISC SHALL BE 1-1/2" DIAMETER, AND ENGRAVED WITH THE WORD "SEWER" CENTERED AT THE 12 O'CLOCK POSITION AND THE WORD "SERVICE" CENTERED AT THE 6 O'CLOCK POSITION ON THE DISC. NAIL AND DISC SHALL BE INSTALLED AT THE EDGE OF PAVEMENT, CURBING OR SIDEWALK DIRECTLY IN LINE WITH THE SEWER SERVICE. THE CITY MAY REQUIRE OTHER MEANS OF IDENTIFICATION, SUCH AS TREATED FENCE POSTS PAINTED GREEN ON TOP TO MARK SERVICES FOR FUTURE DEVELOPMENT.
5. SEE ALSO DETAIL SS-20.



GRAVITY SEWER SERVICE CONNECTION

REVISION DATE:	FEB 2017
NOT TO SCALE	SS-19